

Fast Separation of Oxygen and Nitrogen on a MolSieve 5A Channel Using the Agilent 490 Micro GC

Application Note

Micro Gas Chromatography, Permanent Gas Analysis

Authors

Mohamed Bajja and Remko van Loon Agilent Technologies, Inc. Middelburg The Netherlands



Introduction

When a really fast separation of Oxygen and Nitrogen is required, the Agilent 490 Micro GC, equipped with a short MolSieve 5A column channel, delivers the speed you need.

This application note shows the fast separation of Oxygen and Nitrogen using a 4 m MolSieve 5A column channel instead of using the standard 10 m MolSieve 5A column channel. The advantage of the Agilent 490 Micro GC, in combination with this 4 m MolSieve 5A column channel, is the ease-of-use and the speed of analysis. Nitrogen will elute in less than 20 s.

Argon and Oxygen will not be separated on the 4 m MolSieve 5A column. These compounds will coelute. The separation of Argon and Oxygen requires the use of a 20 m MolSieve 5A column channel on a low temperature.

The Agilent 490 Micro GC is a rugged, compact and portable lab-quality gas analysis platform. When the composition of gas mixtures is critical, count on this fifth generation micro gas chromatography.



Instrumentation

Instrument Agilent 490 Micro GC (G3581A)

Column channel MolSieve 5A, 4 m

Column temperature 100 °C


Carrier gas Helium, 100 kPa Injection time 40 msec

Sample information

 Hydrogen
 1.0%

 Oxygen
 0.4%

 Nitrogen
 0.2%



For More Information

These data represent typical results. For more information on our products and services, visit our Web site at www.agilent.com/chem.

www.agilent.com/chem

Agilent shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

Information, descriptions, and specifications in this publication are subject to change without notice.

© Agilent Technologies, Inc., 2011 Printed in the USA June 28, 2011 5990-8529EN

